





ISUZU NOVOCITI LIFE


Manufactured by Anadolu Isuzu


The one and only "Isuzu Manufacturing Management (IMM)" certified Isuzu factory in Europe.

NOVOCITI LIFE

TECHNICAL SPECIFICATIONS

TECHNICAL OF ECH ICATIONS		
Dimensions (mm)		
Maximum Length	7863 (8010 Optional)	
Maximum Width	2435	
Maximum Height	3184 (w/AC)	
Wheelbase	4259	
Front Overhang	1945	
Rear Overhang	1806	
Weights (kg) Gross Vehicle Weight	10.755	-
oross verificie weight	10.755	
Engine	EDT VIEW (D	
Model	FPT NEF4 (Rear)	
Туре	Electronic Common Rail, Turbo Diesel Intercooler	
Number of cylinders	4	
Engine volume (cm3)	4500	
Maximum power (kW (HP) /rpm)	137 (186) @ 2500 rpm	
Maximum torque (Nm/rpm)	680 Nm @ 1400 rpm	
Transmission		-
Model	A/T: ALLISON 2100 (S),	
	A/T: ALLISON 3270R (Opt)	
	M/T: ZF 6S 1010 B0 (Opt)	
Tyres		
•	215/75 R17,5	
Suspensions	Air Sugnancian 2 Air Pollows	
Rear	Air Suspension - 2 Air Bellows Air Suspension - 4 Air Bellows	
Kneeling System	S	
• ,	3	
Brake System	Diag / Diag	-
Front / Rear System	Disc / Disc ABS. ASR	
Service	Full Air Brake System, Dual Circuit	Floctronical actuato
Auxiliary Brake	Turbo Brake and Optional Retarder	
·	Tarbo Brake and Optional Netarael	
Fuel Tank Canacity (It)	130	-
Fuel Tank Capacity (lt) Diesel Exhaust Fluid Tank(lt)	30	
	30	
Electrical System	0 ()/ (0)/4 () () 4 () 5 ()	
Battery	24V (2X12V) - 125 Ah	
Passenger Capacity*		
	21(Seated) + 39(Standing) = 60	







DVD Player

ENLIPMENTS

EQUIPMENTS		ANADOLU
General Digital Tachograph	Opt	ISUZU
Heating and Ventilation	·	
Pre-heater	Opt	
Heater (Front/Middle/Rear)	S	
Air Conditioner		
Digital Air Conditioner	S (27,5 kW)	
A/C with Heater	Opt	
Safety & Driving Comfort		201
Roof emergency escape hatch &	C (Flooring)	non-
roof ventilation hatch	S (Electrical)	
Parking Sensor Rear view camera	Opt Opt	Č
Interior Camera	Opt Automatic fire extinguisher system at engine room	Opt
Exterior camera	Opt Engine room fire detect and driver alert system	S
Retarder	Opt Fire extinguisher	Opt g
ABS	S Speed limitor	S
ASR	S Reverse Gear Warning Beeper	S
Exterior		e e e e e e e e e e e e e e e e e e e
Daytime Running Lamps (DRL)	S	w with
Front and Rear Fog Lamps	S	ucts
Towing Device	S	000
Metallic Paint	Opt	the the
Doors	Facati Cicale Wine Decomposite Insured Codes	an of
Type of Service Doors	Front: Single Wing, Pneumatic, Inward Swing, Rear: Double Wings, Pneumatic, Outward Swing,	 8 9
	Auto-locking System Over 5 km/h Speed (Opt)	the
Disabled Passenger Access	S	and
Remote Control for Front Door	S	000
Windows		icati
Driver's Window	Single Glazed with Heater	
Blind	S	SS
Passenger Windows	Single glass standard Sliding windows both at right and left sides	S S do
Single Glazing	S	an de
Hinged window	S	e Ch
Interior Driver Seat		aa B
Driver's Seat	Air actuated, Adjustable, With Headrest	t to
Driver's Cabin	Opt	<u> </u>
Ticket Box Pre-arrangement	Opt	the
Passenger Compartment		SILVe.
Seat Material	Cloth Ped On Plastic	rese
Interior Lining (Ceiling)	Viynl	nzn
Sidewall Lining	ABS	<u>s</u>
Interior Lighting (Ceiling)	6 Units	ope
Audio & Visual		4
Stop Sign (Interior)	S LED to a chicago (Fount and Cide) (C)	
Digital Destination Indicators	LED-type Headsign (Front and Side) (S), Rear Indicator Panel (Opt), Colored Headsign (Not Rounding) (O	nt)
High-Drive Mode	S	pt)
LCD Screen	Opt	
Digital Clock	S S: Standard Opt: Optional	
DVD Dlaves	Ont * Different coating variations are availa	ANADOLLI GROLIP

Opt



* Different seating variations are available.